


Water level and temperature indicator with rounded cable, four copper wires, kevlar core and external anti-scratch protective film in transparent PUR.

Graduation in centimeters, printed in black on the cable itself, with meter/decimeter indication.

- Graduation: 1 cm
- Rounded cable diameter: 5 mm
- Probe diameter: 10 mm, made of stainless steel and moulded rubber, with segmented weights for more flexibility (suitable also for small diameter piezometric holes)
- Acoustic signal and red LED indicate the water level
- Temperature display (Pt100 sensor accuracy +/- 0.1%, range from -10°C to +50°C)
- 1x9V battery, easy external access
- Optional removable hook for bailer
- Available lengths: from 30 to 500 m



Cable detail ↑

WMS-02 panel with temperature display ↓



Removable hook for bailer (the probe can be inserted in the sampler)



WMS-02 AVAILABLE MODELS

modell	cable length	cable reel	dimension in cm	weight	order code
WMS-02-30	30m	PVC	L25cm xP18cm xH35cm	1,5	FRE-029-000
WMS-02-50	50m	PVC	L25cm xP18cm xH35cm	2	FRE-030-000
WMS-02-100	100m	PVC	L25cm xP18cm xH35cm	3	FRE-031-000
WMS-02-150	150m	METAL	L32cm xP22cm x H40cm	5	FRE-032-000
WMS-02-200	200m	METAL	L32cm xP22cm x H40cm	6	FRE-033-000
WMS-02-300	300m	PVC	L49cm xP36cm x H59cm	13	FRE-034-000
WMS-02-400	400m	PVC	L49cm xP36cm x H59cm	15	FRE-035-000
WMS-02-500	500m	PVC	L49cm xP36cm x H59cm	17	FRE-036-000