

Smart Level Transmitter with Low Power Consumption & Digital Output

MPM4706



Applications

- Medicine, metallurgy
- Power plants, mines
- Urban water supply and drainage
- Hydrological exploration

Features

- Extremely low power consumption, automatic sleep
- Pressure and temperature measurement
- Digital temperature compensation and non-linear correction technology
- RS485 communication interface
- Networking applications

Introduction

MPM4706 Smart Level Transmitter is a fully sealed, submersible measuring instrument constructed of stainless steel. It utilizes a high-stability piezoresistive OEM pressure sensor and a high-precision smart processing circuit, along with proprietary algorithms, to achieve accurate measurements. Equipped with a digital temperature sensor, the device measures ambient or medium temperatures and outputs data via an RS485 interface. Designed for low power consumption, it automatically enters a sleep mode during periods of inactivity, reducing consumption to below 10μA.

Specifications

Range	
Overpressure	Refer to "Measuring Range & Accuracy Table"
Accuracy	
Pressure type	Gauge pressure
Temperature accuracy ^a	±0.5°C (-20°C ~ 80°C)
Long-term stability	≤±0.25% FS/ year
Compensation temperature	-10°C ~ 70°C
Operating temperature	-20°C ~ 70°C (cable material: PE, PVC) -20°C ~ 80°C (cable material: PUR)
Storage temperature	-20°C ~ 85°C
Vibration	20g, 20Hz ~ 5000Hz
Shock	20g, 11ms
IP rating	IP68
Weight	≤ 250g (excluding cable weight)

^a Temperature accuracy: The measured temperature is the ambient temperature.


Measuring Range & Accuracy Table

Gauge Pressure G				
Unit	Measuring Range	Accuracy	Overpressure	Code
mH ₂ O	0 ~ 1	±0.5%FS	4	H001
	0 ~ 2	±0.25%FS	4	H002
	0 ~ 2.5		4	H2D5
	0 ~ 3		7	H003
	0 ~ 3.5		14	H3D5
	0 ~ 4		14	H004
	0 ~ 5		20	H005
	0 ~ 6		20	H006
	0 ~ 7		20	H007
	0 ~ 8		20	H008
	0 ~ 9		20	H009
	0 ~ 10		20	H010
	0 ~ 15		40	H015
	0 ~ 20		40	H020
	0 ~ 25		70	H025
	0 ~ 30		70	H030
	0 ~ 35		70	H035
	0 ~ 40		140	H040
	0 ~ 45		140	H045
	0 ~ 50		140	H050
	0 ~ 60		140	H060
	0 ~ 70		140	H070
	0 ~ 80		200	H080
	0 ~ 90		200	H090
	0 ~ 100		200	H100
	0 ~ 110		400	H110
	0 ~ 120		400	H120
	0 ~ 150		400	H150
	0 ~ 200		400	H200

Note: The specified accuracy applies within the compensation temperature range of -10°C to 70°C.
Test standard: GB/T 17614.1-2015/IEC60770-1:2010

Unit mm

Outline Construction



Output Signals

Output signal	Supply voltage	Output type	Load resistance
RS485, ASCII communication protocol (R4)	3.6V~28V DC	4-wire	The RS485 bus supports up to 99 devices.
RS485, MODBUS_RTU communication protocol (R8)			

Electrical Connection

Color	4-wire
Red	(+V)
White	RS485B
Black	(-V)
Yellow (Green)	RS485A
Blue	Ground wire

Auxiliary Software


RS485 Transmitter software

47XX software

Used with an RS485 converter module, this software enables reading basic internal information from RS485 transmitters (including level range, temperature compensation range, version, etc.), display the actual level, set a new zero, configure the programmable analog output, and set the device address.

Note: The “47XX” programming software is available for download from our official website: www.microsensorcorp.com.

Sensor Sealing




Construction Materials

Isolated diaphragm: SS 316L/Titanium

Housing: SS 304/ SS 316L/Titanium

Cable: PE/PUR/PVC



Order Guide

MPM4706	Smart Level Transmitter									
	Range	Measuring range 0mH2O ~ 1mH2O...200mH2O								
	HXXX	Range-specific code								
		Code	Output signal							
		R4	RS485, ASCII							
		R8	RS485, MODBUS_RTU							
			Code	Power supply						
			V15	3.6V ~ 28V DC						
				Code	Accuracy					
				A1	±0.25%FS					
				A2	±0.5%FS					
					Construction material					
				Code	Isolated diaphragm				Housing	
				22	Stainless steel 316L				Stainless steel 304	
				24	Stainless steel 316L				Stainless steel 316L	
				40	Titanium TA1				Titanium TC4	
					Code	Sensor sealing				
					00	FKM (standard)				
					01	EPDM (optional for special media based on compatibility)				
					02	Welding (optional for special media based on compatibility)				
					Code	Cable material				
					P1	PE (standard)				
					P2	PUR (optional for special media based on compatibility)				
					P3	PVC (optional for special media based on compatibility)				
						Code	Cable length (Unit: m)			
						L001	1			
						L002	2			
						L003	3			
						L004	4			
						L005	5			
						L006	6			
						L007	7			
						L008	8			
						L009	9			
						L010	10			
						L012	12			
						L015	15			
						L017	17			
						L020	20			
						L30	30			
						L035	35			
						L040	40			
						L045	45			
						L050	50			
MPM4706	H005	R8	V15	A1	22	00	P3	L005	The complete spec.	

Order Guide

Code	Cable length (Unit: m)
L060	60
L070	70
L080	80
L090	90
L100	100
L110	110
L120	120
L150	150
L200	200

Code	Accessory
N	No accessories required
Yb5	Yb junction box (5-core terminals)
Yc5	MS200 (5-core terminals)
Yd	PD140
Ye	Ye (without indicator)
MS01	Polymer plug

Ye

The complete spec.

Notes

- 1.The measured medium shall be compatible with the wetted parts materials, and the medium's density (excluding water) under measurement conditions must be specified.
- 2.In areas prone to thunderstorms, install lightning protection and ensure proper grounding of the product and power supply to minimize lightning damage to the transmitter.
3. If a metrology verification certificate is required, or there are any other special requirements, please consult with the MICROSENSOR and specify them in the order.

ООО “РусАвтоматизация”

454010 г. Челябинск, ул. Гагарина 5, оф. 507
 тел. 8-800-775-09-57 (звонок бесплатный), +7(351)799-54-26, тел./факс +7(351)211-64-57
info@rusautomation.ru; русавтоматизация.рф; www.rusautomation.ru