



# XSON-SUP-1158S Fixed Separated Ultrasonic Flowmeter

The fixed separated model is inline measurement for long-term.

There are 3 types converters including wall mounted, panel mounted and proof-explosion.

Convertors can be installed at indoor or instrument cabinet Transducers should be installed on the measuring pipe; Converter and transducer be connected by cable.



## | Features |







- **High Accuracy**  
1%
- **Wide measuring range**  
Several types transducer for selection, pipe size from Dn15mm to Dn6000mm
- **High Reliability**  
Adopt low voltage, multi-pulse technology to improve accuracy, useful life and reliability.
- **Strong Anti-interference**  
Dual-balance signal differential receiver/driver circuit to avoid interference of converter, TV tower, high voltage line etc.
- **Powerful Recording Function**  
Automatically record the following data:
  1. The totalizer data of the last 512 days/128 months/10 years
  2. The time and corresponding flow rate of the last 64 times of power on and off events
  3. The working status of the last 32 days
- **Support Heat Measurement**  
Connect the temperature transducer, can finish the heat/energy measurement
- **Support SD card Memory**  
Optional SD card

# XSON-SUP-1158S Fixed Separated Ultrasonic Flowmeter

## | Liquid Type |

This flowmeter can be virtually applied to a wide range of measurement. A variety of liquid applications can be accommodated: ultra-pure liquids, potable water, chemicals, raw sewage, reclaimed water, cooling water, river water, plant effluent. etc

## | Measuring Diagram |

Flow Measurement	Heat Measurement	Features
 <p>Clamp on</p>	 <p>Supply Pipe Return Pipe</p>	<ul style="list-style-type: none"> <li>• No need to cut off water , no pressure loss</li> <li>• Easy for installation</li> <li>• Connect clamp on temperature transducer, can finish the heat/energy measurement</li> </ul>
 <p>Insertion</p>	 <p>Supply Pipe Return Pipe</p>	<ul style="list-style-type: none"> <li>• No need to cut off water , no pressure loss</li> <li>• Stable and reliable for long term operation</li> <li>• Connect Pt100 temperature transducer, can finish the heat/energy measurement</li> </ul>
 <p>Pipe</p>	 <p>Supply Pipe Return Pipe</p>	<ul style="list-style-type: none"> <li>• Need to cut off pipe</li> <li>• With high accuracy and stability</li> <li>• Connect Pt100 temperature transducer, can finish the heat/energy measurement</li> </ul>

## | Optional Converter |

According to different installation condition, pls choose relative convertor














- Wall mounted XSON-SUP-1158 SW
- Wall mounting installation
- Dimension : 170×180×56mm
- Power supply: DC8~36V or AC85~264V







- Panel mounted XSON-SUP-1158 SS
- Instrument cabinet installation
- Dimension : 170×180×56mm
- Hole-opening dimension 152×76mm
- Power supply: DC8~36V or AC85~264V

# XSON-SUP-1158S Fixed Separated Ultrasonic Flowmeter

## | Optional Transducers |

Types	Picture	Spec.	Model	Measurement Range	Temperature	Dimension
Clamp on		Small Size	XSON-TS-2	DN15~DN100	-30~90°C	45×25×32mm
		Medium Size	XSON-TM-1	DN50~DN700	-30~90°C	64×39×44mm
		Large Size	XSON-TL-1	DN300~DN6000	-30~90°C	97×54×53mm
High temp clamp on		Small Size	XSON-TS-2-HT	DN15~DN100	-30~160°C	45×25×32mm
		Medium Size	XSON-TM-1-HT	DN50~DN700	-30~160°C	64×39×44mm
		Large Size	XSON-TL-1-HT	DN300~DN6000	-30~160°C	97×54×53mm
Insertion		Standard	XSON-TC-1	DN80~DN6000	-30~160°C	190×80×55mm
		Lengthen	XSON-TC-2	DN80~DN6000	-30~160°C	335×80×55mm
Pipe		π type	XSON-G3	DN15~DN25	-30~160°C	Pls refer to detailed pipe dimensions
		Standard	XSON-G2	DN32~DN40	-30~160°C	
		Standard	XSON-G1	DN50~DN6000	-30~160°C	


## | Optional Temperature Transducers |

Picture	Specification	Model	Meas.Range	Temperature	Cut of water	Accuracy
	Clamp on temperature Transducer Pt100	XSON-CT-1	≥DN50	-40~160°C	No	100°C ± 0.8°C
	Insertion temperature Transducer Pt100	XSON-TCT-1	≥DN50	-40~160°C	Yes	
	Insertion Pt100 Installation with pressure	XSON-PCT-1	≥DN50	-40~160°C	No	
	Insertion Pt100 Small size pipe diameter	XSON-SCT-1	<DN50	-40~160°C	Yes	

## | Optional SD card memory |


The SD card memory can be expanded to 2GB, which can achieve the ultrasonic flowmeter measurement data mass storage, can solve the problems for wall-mounted flowmeter measurement data stored, reading, and processing inconvenience. can completely replace manual meter reading, no paper records instrument.

In addition, the SD memory card measurements data, can be used by our company's "Flow data analysis, statistical software" for processing, including the tabulation, statistical, data analysis, printing reports, production flow curve




SD card memory of wall mounted

- Raw Data




- Software Import Data



- Instantaneous Flow Curves Generated by Software



- Cumulative Flow Bar Chart Generated by Software



# XSON-SUP-1158S Fixed Separated Ultrasonic Flowmeter

## | Datasheet |

Items		Performance & Parameter
Converter	Principle	Transit-time ultrasonic flowmeter
	Accuracy	±1%
	Display	2×20 character LCD with backlight, support the language of Chinese, English and Italy
	Signal Output	1 way 4~20mA output, electric resistance 0~1K, accuracy 0.1%
		1 way OCT pulse output (Pulse width 6~1000ms, default is 200ms)
		1 way Relay output
	Signal Input	3 way 4~20mA input, accuracy 0.1%, acquisition signal such as temperature, press and liquid level
Connect the temperature transducer Pt100, can finish the heat/energy measurement		
Data Interface	Insulate Rs485 serial interface, upgrade the flowmeter software by computer, support the MODBUS	
Special Cable	Twisted-pair cable, generally, the length under 50 meters; Select the RS485, transmission distance can over 1000m	
Pipe Installation Condition	Pipe Material	Steel, Stainless steel, Cast iron, Copper, Cement pipe, PVC, Aluminum, Glass steel product, liner is allowed
	Pipe Diameter	15~6000mm
	Straight Pipe	Transducer installation should be satisfied: upstream 10D, downstream 5D, 30D from the pump
Measuring Medium	Type of Liquid	Single liquid can transmit sound wave, such as Water (hot water, chilled water, city water, sea water, waste water, etc.); Sewage with small particle content; Oil (crude oil, lubricating oil, diesel oil, fuel oil, etc.); Chemicals (alcohol, etc.); Plant effluent; Beverage; Ultra-pure liquids, etc.
	Temperature	-30~160°C
	Turbidity	No more than 10000ppm and less bubble
	Flowrate	0~±7m/s
Working Environment	Temperature	Converter: -20~60°C; Flow Transducer: -30~160°C
	Humidity	Converter: 85%RH; Flow Transducer: can measure under water, water depth ≤2m (transducer sealed glue)
Power Supply	DC 8~36V or AC 85~264V (optional)	
Power Consumption	1.5W	
Dimension	170*180*56cm (converter)	

## | Ordering Code |

XSON-SUP-1158S	Converter	Flow Transducer	Diameter	Pipe Material	Pressure	Cable Length	Temperature Transducer	SD card Memory
	□	□	□ DN □ mm	□	□ MPa	□ m	□	□
	W	TS-2		0 Carbon Steel			None	0 Yes
	S	TM-1		1 Stainless Steel			CT-1	1 No
	D	TL-1		2 Cast Iron			TCT-1	
		TS-2-HT		3 Glass Fiber reinforced			PCT-1	
		TM-1-HT		4 PVC			SCT-1	
		TL-1-HT		5 Cement				
		TC-1		6 Others				
		TC-2						

G

Example XSON SUP-1158SW+TM-1+DN300+0+1.6MPa+10m+PCT-1+0

PS: Standard configuration=XSON SUP-1158SW(converter)+TM-1+5M cable + Steel belt (DN200) + Couplant(1 pc)

### ООО "РусАвтоматизация"

454010 г. Челябинск, ул. Гагарина 5, оф. 507

тел. 8-800-775-09-57 (звонок бесплатный), +7(351)799-54-26, тел./факс +7(351)211-64-57

[info@rusautomation.ru](mailto:info@rusautomation.ru); [rusavtomatizatsiya.ppf](mailto:rusavtomatizatsiya.ppf); [www.rusautomation.ru](http://www.rusautomation.ru)